

SPF2/MS

Code: SPELSPF2MS

SKIVING - SPELLATURA



SPF2/E

Code: SPELSPF2/E

SKIVING - SPELLATURA



SPF1

Code: SPELSPF1

SKIVING - SPELLATURA



MAIN FEATURES - CARATTERISTICHE PRINCIPALI



Internal skiving

Spellatura interna



External skiving

Spellatura esterna



Pneumatic vice

Morsa pneumatica

SPF2/MS



Safety protections

Protezioni di sicurezza

SPF2/E
SPF2/MS



Drawer for shavings

Cassetto porta trucioli

SPF2/E
SPF2/MS



Also available in 12V

Disponibile anche in 12V

SPF2/E



Ideal for on-site service

Ideale per il service

SPF2/E
SPF1

TECHNICAL DATA - DATI TECNICI

	SPF2/MS	SPF2/E	SPF1
EXTERNAL SKIVING CAPACITÀ Ø ESTERNO	2"	2"	2"
INTERNAL SKIVING CAPACITÀ Ø INTERNO	2"	2"	2"
REVOLUTIONS/MINUTE GIRI AL MINUTO	300	300	-
PNEUMATIC INPUT ALIMENTAZIONE PNEUMATICA	MAX 7 Bar (100 Psi) OPTIONAL	-	-
WEIGHT PESO	78 Kg	50 Kg	7 Kg
DIMENSIONS LxWxH DIMENSIONI LxPxH	685x500x1120 mm	675x535x437 mm	480x240x100 mm
STANDARD VOLTAGE VOLTAGGIO STANDARD	400V 50HZ 3PH	400V 50HZ 3PH	-
MOTOR POWER POTENZA DEL MOTORE	0.75 Kw (1 Hp)	0.75 Kw (1 Hp)	-

ACCESSORIES - ACCESSORI

		SPF2/MS	SPF2/E	SPF1
ELECTRIC PEDAL (INCLUDED) PEDALE ELETTRICO (INCLUSO)		■	■	-
TOOL HOLDER PORTAUTENSILI		■	■	■
TOOL HOLDER STAND MOBILE PORTAUTENSILI		■	-	-

SPF2/MS



SINGLE MANDREL FOR EACH DIAMETER SHARP WITH DOUBLE KNIFE

SPF2/MS




PNEUMO-HYDRAULIC VICE
OPTIONAL
MORSA PNEUMO-IDRAULICA
OPTIONAL

SPF2/E



FIXED SKIVING MANDREL WITH ONE CUTTER ONLY, PROVIDED WITH A MILLIMETRIC RULER TO SET THE SKIVING DISTANCE
MANDRINO DI SPELLATURA FISSO CON UN TAGLIENTE E RIGA DI CARTA MILLIMETRATA PER IMPOSTARE LA DISTANZA DI SPELLATURA

SPF1



SPF2/E



DRAWER FOR SHAVINGS
CASSETTO PORTA TRUCIOLI